

SLIM-DUAL-LUNA-PET

SLIM-DUAL-LUNA-PET detects motion in the protected area. Additionally, the detector has a set of LEDs to implement the lighting feature.

- certificate of compliance with the EN 50131 requirements for Grade 2
- motion detection using two sensors: a passive infrared (PIR) sensor and a microwave (MW) sensor
- adjustable detection sensitivity of both sensors
- option to test the sensors separately
- digital motion detection algorithm
- digital temperature compensation
- digital filter of signals received by the microwave sensor to ensure immunity to false alarms caused by the power network and discharge lamps
- operating mode selection: basic, advanced, PIR or MW
- wide-angle lens, designed specifically for **SLIM LINE** detectors
- pet immunity up to 20 kg (basic operating mode only)
- ability to configure detector operating parameters using the **OPT-1** keyfob
- built-in end-of-line resistors (2EOL: 2 x 1,1 kΩ / 2 x 4,7 kΩ / 2 x 5,6 kΩ)
- lighting feature implemented with white LEDs
- remote lighting control or motion activated lighting capability
- LED indicator
- selectable color of LED indicator (7 colors available)
- LED indicator remote enable/disable
- remote switching between two sets of detector operating parameters
- configuration mode remote enable/disable
- supervision of motion detection and supply voltage circuit
- tamper protection against opening of enclosure and removal from mounting



Alarm signaling time	2
Relay contact resistance (tamper output)	26
Relay contact resistance (alarm output)	26
Tamper outputs (NC relay, resistive load)	40 mA / 24 V DC
Alarm outputs (NC relay, resistive load)	40 mA / 24 V DC
Detection area	12 m x 13 m, 90°
Warm-up period	30
EOL resistors	2 x 1,1 kΩ / 2 x 4,7 kΩ / 2 x 5,6 kΩ
Security grade according to EN50131-2-4	Grade 2
Microwave frequency	24,125
Complied with standards	EN 50131-1, EN 50131-2-4, EN 50130-4, EN 50130-5
Supply voltage	12
Environmental class according to EN50130-5	II
Dimensions	62 x 137 x 42
Maximum humidity	93±3%
Weight	144
Max. current consumption	100
Standby mode current consumption	14
Recommended mounting height	2,4
Operating temperature range	-10°C...+55°C
Detected target velocity	0,3...3